

ケーブル仕様ガイド

UL2464 Multi-Conductor Cable

■ Technical Data

UL Style& CSA Type	ゲージ	Conductor		絶縁被覆の 厚さ	ジャケットの 厚さ	直径	静電容量		抵抗値 (20℃)
		No./OD	芯数				A	B	
	AWG	No./mm		mm	mm	mm			Ω/KM
UL2464CSA AWM I/II A (Stranded)	28	7/0.10	3	0.25	0.80	3.70	28	51	239.00
			4	0.25	0.80	3.90	28	51	
			5	0.25	0.80	4.20	28	51	
			6	0.25	0.80	4.50	26	47	
			7	0.25	0.80	4.50	26	47	
			8	0.25	0.80	4.80	26	47	
			9	0.25	0.80	5.10	26	47	
			10	0.25	0.80	5.20	26	47	
			15	0.25	1.00	5.80	26	47	
			25	0.25	1.00	7.60	26	47	
			37	0.25	1.00	8.30	26	47	
UL2464CSA AWM I/II A (Stranded)	26	7/0.16	3	0.25	0.80	3.90	32	52	150.00
			4	0.25	0.80	4.20	32	52	
			5	0.25	0.80	4.50	32	52	
			6	0.25	0.80	4.80	28	51	
			7	0.25	0.80	4.80	28	51	
			8	0.25	0.80	5.10	28	51	
			9	0.25	0.80	5.40	28	51	
			10	0.25	0.85	5.70	28	51	
			15	0.25	1.00	6.40	28	51	
			25	0.25	1.00	8.00	28	51	
			37	0.25	1.00	9.20	28	51	
UL2464CSA AWM I/II A (Stranded)	24	11/0.16	3	0.25	0.80	4.20	33	65	94.20
			4	0.25	0.80	4.50	33	65	
			5	0.25	0.80	4.90	33	65	
			6	0.25	0.80	5.20	33	65	
			7	0.25	0.80	5.20	33	65	
			8	0.25	0.80	5.50	33	65	
			9	0.25	0.85	5.80	30	55	
			10	0.25	0.85	6.20	30	55	
			15	0.25	0.85	6.90	30	55	
			25	0.25	1.00	8.60	30	55	
			37	0.25	1.00	9.80	30	55	
UL2464CSA AWM I/II A (Stranded)	22	7/0.25	3	0.25	0.80	4.70	37	67	59.40
			4	0.25	0.80	5.10	37	67	
			5	0.25	0.80	5.50	37	67	
			6	0.25	0.80	5.80	35	63	
			7	0.25	0.80	5.80	35	63	
			8	0.25	0.85	6.30	35	63	
			9	0.25	0.85	6.70	35	63	
			10	0.25	0.85	6.80	35	63	
			15	0.25	0.85	7.80	35	63	
			25	0.25	1.00	10.00	35	63	
			37	0.25	1.00	11.30	35	63	
UL2464CSA AWM I/II A (Stranded)	18	34/0.178	2	0.25	0.80	5.80	70	120	23.20
			3	0.25	0.80	6.00	70	120	
			4	0.25	0.80	6.70	70	120	
			5	0.25	0.80	7.30	70	120	